

XUV probing of laser imprint using an Yttrium x-ray laser*

D.H. Kalantar, L.B. DaSilva, S.G. Glendinning, M.H. Key¹, F. Weber, and S.V. Weber, *Lawrence Livermore National Laboratory*, and J.P. Knauer, *Laboratory for Laser Energetics, University of Rochester* - For direct drive ICF, a capsule is imploded by directly illuminating the surface with laser light. Beam smoothing and uniformity of illumination affect the seeding of instabilities at the ablation front. We have developed a new technique for studying the imprint of a laser beam on a thin Si foil. We use an Yttrium x-ray laser as an XUV backlighter. This is relayed via multilayer optics onto a Si foil that is irradiated by a low intensity 0.35 μm laser beam. The foil is imaged onto a CCD camera to measure the optical depth modulation in the foil due to laser imprint. By using the XUV backlighter to radiograph a Si foil, we are able to measure small fractional variations in the foil thickness. We recorded images due to imprint from a $5 \times 10^{12} \text{ W/cm}^2$ drive beam incident on a 3 μm Si foil at the time the shock launched by the ablation pressure breaks out at the back of the foil. We compare the cases of a static speckle pattern due to a random phase plate beam with a broad bandwidth SSD smoothed speckle pattern. We compare both cases with Lasnex simulation.

¹ On leave from Rutherford Appleton Laboratory, UK.

* Work was performed under the auspices of the U.S. Department of Energy by the Lawrence Livermore National Laboratory under Contract No. W-7405-ENG-48.